WAVE PTX RADIO VAVE PTX RADIO TLX 150 RAPID, RELIABLE DEPLOYMENT.

EASY TO USE AND MANAGE BUILT FOR THE JOB - SAFELY OPERATE IN VEHICLE EUROPE-WIDE* PUSH-TO-TALK

Get your team up and running quickly. Combine the broad coverage of a Europe-wide broadband network* with the ease of push-to-talk radio communications.

USE EUROPE-WIDE^{*}.

Safely operate while driving with one button push-to-talk. Manage talk groups and subscriptions in real time. Increase coverage, connections, and productivity without expanding infrastructure.

There's no costly or time-consuming spectrum licensing, or manual programming required.

FEATURE HIGHLIGHTS

СН

A MOTOROL

- Private and group push-to-talk
- Over-the-air device management
- 4G LTE, 3G and Wi-Fi connectivity
- GPS location tracking

*Z * ♥

Ai

Dispatch

Ellox (P1 P2) DR

- Loud and clear audio
- Real-time presence
- Bluetooth® enabled
- 12V/24V dual voltage support



GENERAL SPECIFICATIONS


Network	4G LTE: 1,2,3,4,5,7,8,13,17,19,20,21,28		
Network	3G UMTS: 1,2,5,8		
Channel Capacity	96 Channels		
Contact List	300 contacts		
Dimensions (W x H x L)	169mm x 44mm x 93mm		
Weight	640 g		
Voice Codec	OPUS		
Wi-Fi	802.11 a/b/g/n - 2.4 / 5.0 GHz		
Bluetooth	Bluetooth V4.2 BR/EDR + BLE		
Location	GNSS / A-GPS (GPS, GLONASS, Galileo, BeiDou)		
IP Rating	IP54 IEC60529		
Apps Supported	Powered by WAVE PTX		
Encryption	AES-256		
Antennas	LTE antennas - External GNSS antenna - External Wi-Fi/Bluetooth antenna - Internal		
Connectors	Front RJ45 connector for wired mobile microphone Back antenna SMA connectors Back 20-pin MAP connector for other accessories		
Rated Audio	4 W (Internal) 16 W (External - 4 ohms)		
Audio Distortion @ Rated Audio	3% (Typical)		

ENVIRONMENTAL SPECIFICATIONS				
Operating Temperature	-20°C to +60°C			
Storage Temperature	-40°C to +85°C			
Thermal Shock	Per MIL STD-810			
Humidity	Per MIL STD-810			
ESD	IEC61000 - 4-2 Level 4			
Dust and Water Intrusion	IEC60529 - IP54 Cat 2			
Packaging Test	Per MIL STD-810			

APPLICABLE U.S. MILITARY SPEC RATINGS				
MIL 810G STANDARD**	METHOD	PROCEDURES		
Low Pressure	500.5	I, II		
High Temperature	501.5	I, II		
Low Temperature	502.5	I, II		
Temperature Shock	503.5	I, II		
Solar Radiation	505.5	I-C		
Rain Blowing	506.5			
Dust Blowing	510.5			
Immersion	512.5	I		
Vibration	514.6			
Shock	516.6	LIV		

**Also meets equivalent MIL-STD-810-C, -D, -E and -F





TLK 150 ACCESSORIES



PUSH-TO-TALK SOLUTIONS

Make communicating easier and safer with these optional accessories from a simple PTT microphone to a complete hands free solution.

PMMN4129	Wideband Compact Mobile Microphone
GMMN4065	Visor Microphone
RLN4856	Footswitch Push-to-Talk
RLN4857	Remote Mount Pushbutton Push-to-Talk
RLN4836	Emergency Footswitch
PMMN4127	WM500 Bluetooth Remote Speaker Microphone



EXTERNAL SPEAKER

Boost audio	ati	JOUR	wor	ketation	٥r	in	vour	vohic	ما
DOO2L GUUID	dl	your	WUI	KSLOLIUII	UI	ш	yuui	venic	IE.

AC000240A01 Wideband External Speaker, 13 W

ANTENNAS	
AN000359A01	GNSS Dash Mount Antenna
AN000358A01	LTE Dash/Glass Mount Antenna



WOUNTING AGGESSONIES				
Choose where to mount the radio without compromising safety.				
Low Profile Trunnion Kit				
High Profile Trunnion Kit				
Key Lock Trunnion Mount				
In-Dash Mounting Kit - DIN				
Microphone Hang-Up Clip (install by screwing to convenient surface)				
Universal Microphone Hang-Up Clip (no installation required)				

DESKTOP ACCESSORIES		
Mounting aids for use in desktop control stations.		
GLN7318	Desktop Tray Without Speaker	
PMPN4076	Desktop Wedge Tray With Built-in Power Supply	
A range of cables to connect the power supply and TLK 150 are available.		


Talk to your authorised Motorola Solutions reseller for more information.

CABLES AND ACCESSORIES		
HKN4137	DC Power Cable With Inline Fuse 3m/10ft, 15A	
HKN9327	Ignition Switch Cable	
HLN9457	16 Pin MAP Connector Kit	
HKN4192	Battery Power Cable (6m / 20ft, 20 A)	
GMKN4084	Speaker Extension Cable	



YOUR PATH TO EUROPE-WIDE* PTT

PLACE YOUR ORDER, GET YOUR RADIO AND START TALKING



WARRANTY AND REPAIRS

The TLK 150 radio includes 12 months cover for hardware manufacturing defects as standard, and you have access to software updates and Motorola Solutions technical support for the duration for your WAVE PTX subscription.

For additional peace of mind, we offer optional extended cover to provide hardware repair for three years.

Learn more at www.motorolasolutions.com/WAVEPTX

*Coverage limited to EU only and will vary depending on conditions.

***Configuration is carried out by reseller or reseller may give end user permissions to carry our configuration.

Motorola Solutions Ltd. Nova South, 160 Victoria Street, London, SW1E 5LB, United Kingdom.

Availability is subject to individual country law and regulations. All specifications shown are typical unless otherwise stated and are subject to change without notice. MOTOROLA, MOTO, MOTOROLA SOLUTIONS and the Stylized M Logo are trademarks or registered trademarks of Motorola Trademark Holdings, LLC and are used under license. © 2020 Motorola Solutions, Inc. All rights reserved. (06/20)



